## caroma

CI/SfB | (74.1 | g3 | Date October 2013

Supersedes all previous issues

2.8.13

## Sydney Smart II 305 Easy Height Elongated

1.28/0.8 gpf (4.8/3 I) Water Saving Dual Flush High Efficiency Toilet (HET) Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet









## Sydney Smart II 305 Easy Height Elongated 1.28/0.8 gpf (4.8/3 I) Dual Flush HET

## Two Piece Ultra Low Flush (ULF) Vitreous China Washdown Toilet



A modern concept close coupled washdown 1.28/0.8 gpf (4.8/3 I) Sydney Smart II 305 Easy Height Elongated dual flush high efficiency toilet (HET) featuring unique two button activation providing substantial water saving compared to other HET or standard toilets and smooth rounded contours for easy cleaning. The closet bowl has been designed with a 12" (305 mm) outlet rough-in. The tank incorporates a high performance outlet valve which has been specially developed with the 305 Elongated bowl to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 1.28/0.8 gpf (4.8/3 I) dual flush system, the toilet is suitable for multi-purpose applications where water conservation is important.

Closet bowl: 305 Easy Height Elongated 1.28/0.8 gpf (4.8/3 l) full flush washdown closet bowl with box

flushing rim.

Outlet: Floor mounted 305 elongated outlet connection.

Tank: Sydney Smart II Tank - has a free fitting lid and is suitable for domestic and light commercial

applications.

Weight: 100 lbs (45 kg).

Water Control S

Standard Bottom Entry Tank -- available as left hand inlet and incorporates a super quiet water

control assembly. Internal overflow only.

Fixing: The tank is fixed directly to the closet bowl with a robust base fixing system without the need

for wall fixing.

Colors: White.

**Dimensions:** All dimensions are in inches and millimetres and are subject to normal manufacturing variations.

Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

18-7/8" (480mm) Sydney Smart II 350 Easy Height Elongated Code No. LH inlet 302100W Bowl 305102W (610mm) 9-7/8<sup>3</sup> 250mm  $L_{14-3/8}$ " (365mm) (455mm min.) 3/4" (20mm) approx 17-1/2" Note: All height dimensions to underside of 6-1 closet bowl. Make allowance for bedding. Closet bowl fixing: The closet bowl should be bedded with an approved silicon caulking. Center Line of Outlet